

AC2P Portable Power Station



Specifications

	Area	JP	US	CN	EU/AU/UK
Model	Battery Capacity	230.4Wh/9Ah			
	Cell Type	LiFePO4			
	AC + DC Charging Power	270W Max.			
	Weight	3.6kg/7.9lbs			
	Dimensions(L*W*H)	250*156.5*174.5mm/9.8*6.16*6.87in			
	Charging Temperature	0°C~40°C/32°F~104°F			
	Discharging Temperature	-20°C~40°C/-4°F~104°F			
	Storage Temperature	-20°C~40°C/-4°F~104°F			
	Working Humidity	10%~90%			
AC Output	Power	300W in total			
	Lifting Power	600W			
	Voltage	100VAC	120VAC	220VAC	230VAC
	Current	3A	2.5A	1.36A	1.3A
	Frequency	50Hz/60Hz			
DC Output	Cigarette Lighter Port*1	12VDC/10A			
	USB-A*2	5V/2.4A			
	USB-C*1	5/9/12/15/20VDC,3A;20VDC/5A			
AC Input	Voltage	100VAC	120VAC	220VAC	230VAC
	Max. Current	5.7A	4.8A	2.6A	2.5A
	Frequency	50Hz/60Hz			
	UPS	Switching time ≤20ms			
	Charging Power	270W Max.(0%-80% in 45 minutes @ 10°C-30°C/50°F-86°F)			
	Input Power	570W Max. (pass-through charging, 270W charging power+300W load power)			
DC Input	Interface	XT60PM-M			
	Power	200W Max.			
	Current	8.2A Max.			
	Voltage	12V~28VDC			